

Material Handling Hose

Novaflex 5328

Plaster Hose

A flexible, easy to handle, long lasting, high pressure hose specially designed for use with compatible laster and average.

for use with cement, plaster and gypsum. The cover is ozone and weather resistant and the rubber tube is abrasion resistant. Good for jetting applications.

Construction:

Tube: Black abrasion resistant synthetic rubber Reinforcement: Plies of polyester tire cord Cover: Brown abrasion and weather resistant

synthetic rubber Length: 100 ft

Temperature Range: Up to +180°F (+82°C)

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
5328BS-01250-00	11/4	1.84	4	600	0.97
5328BS-01500-00	11/2	2.09	4	600	1.10
5328BS-02000-00	2	2.72	6	600	1.80
5328BS-02500-00	21/2	3.22	6	600	2.18
5328BS-03000-00	3	3.77	6	500	2.74

Novaflex 5331

Dredge Sleeves/Sand Discharge Hose

A specially compounded abrasive resistant and static conductive tube. This hose is manufactured to very close O.D. tolerances.

Construction:

Tube: Black abrasion resistant synthetic

rubbe

Reinforcement: Polyester tire cord Cover: Black abrasion and weather

resistant synthetic rubber

Length: 20 ft.

Temperature Range: Up to +180°F (+82°C)

5.73 7.25	3/8	4	150	5.45
7.25			130	3.43
7123	3/8	4	150	7.51
8.07	3/8	6	150	9.26
10.19	3/8	8	150	12.97
12.50	1/2	8	150	17.83
14.55	1/2	8	150	22.80
16.04	1/2	12	150	27.21
18.04	1/2	12	150	30.82
	10.19 4 12.50 4 14.55 16.04	10.19	10.19	10.19