

Standard Petroleum Service

Uni-OIL™ GG standard petroleum service hoses are designed for the transfer of a wide range of petroleum products. Uni-OIL™ GG hoses are ideal for transfer of media from storage tanks and process piping to rail cars or tank trucks. Multiple plies of polypropylene films and fabrics are encased in a polyester vapor barrier for superior operation. Rated for full vacuum.

Maximum length: 100 ft. (10" = 80 ft.)
Operating Temperature: -40°F to +212°F (-40°C to +100°C)



ID (INS)	1	1.5	2	3	4	6	8	10
ID (OUT)	1.5	2	2.5	3.5	4.5	7.0	9.4	11.5
Max WP PSI	250	250	250	250	250	250	250	200
Burst Pres PSI	1000	1000	1000	1000	1000	1000	1000	800
Bend Rad. Inches	4.0	5.0	6.0	7.9	11.9	22.0	30.0	40.0
Weight LB/FT	0.6	0.8	1.60	2.40	3.20	7.20	11.0	14.5

Special Petroleum Service

Uni-ZENE™ GG special service petroleum hose is designed to handle modern gasoline additives such as MTBE, ethanol and benzene.

Uni-ZENE™ hoses are built with an effective combination of polyamide, polyester and polypropylene film and fabrics to meet the demands of today's additives. Also recommended for all JP aviation fuels. Rated for full vacuum.

Maximum length: 100 ft. (10" = 80 ft.)
Operating Temperature: -40°F to +250°F (-40°C to +121°C)



ID (INS)	1	1.5	2	3	4	6	8	10
ID (OUT)	1.5	2	2.5	3.5	4.5	7.0	9.4	11.5
Max WP PSI	250	250	250	250	250	250	250	200
Burst Pres PSI	1000	1000	1000	1000	1000	1000	1000	800
Bend Rad. Inches	4.0	5.0	6.0	7.9	11.9	22.0	30.0	40.0
Weight LB/FT	0.6	0.8	1.60	2.40	3.20	7.20	11.0	14.5