

B9 – General Purpose Transfer Hose

Polyurethane Core Tube

Specially formulated polyurethane for increased chemical resistance.



Features

- Excellent flexibility
- Light weight
- Specially Formulated Polyurethane core tube for good chemical compatibility

Construction

- Tube: Specially Formulated Polyurethane
- Reinforcement: Fiber
- Cover: Specially Formulated Polyurethane

Fittings

- 56 Series – pg. E-33 82 Series - Fittings available from Parker Hose Products Division
- For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource
- Access instructions are on pg. G-3

Operating Parameters

- Temperature Range:
 - 40°F (-40°C) to 200°F (93°C)
 - Water/glycol hydraulic fluids limited to 130°F (54°C)
- Vacuum Rating: 28 inch Hg
- Change in length at Max. Working Pressure: +/-2%
- Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Notes

- *Temperature and pressure reduced with 82 series Push-Lok Fitting: -20°F (-29°C) to 100°F (38°C) 100 psi maximum working pressure
- Non-perforated cover

Color

- ● Red
- ● Black (BK) - B904BK

Series B9

[Visit the webpage](#)

| Part Number | Nominal I.D. | | Maximum O.D. | | Maximum Working Pressure | | Minimum Bend Radius | | Weight | | Permanent Fitting Series | Push-Lok Fitting* |
|-------------|--------------|------|--------------|------|--------------------------|-----|---------------------|-------|----------|--------|--------------------------|-------------------|
| | inch | mm | inch | mm | psi | MPa | inch | mm | lbs./ft. | kg/mtr | | |
| B903 | 3/16 | 5 | 0.39 | 9.9 | 250 | 1.7 | 1 | 25.0 | 0.04 | 0.06 | 56 | – |
| B904 | 1/4 | 6.3 | 0.46 | 11.7 | 250 | 1.7 | 1-1/2 | 38.0 | 0.05 | 0.07 | 56 | 82* |
| B905 | 5/16 | 8 | 0.55 | 14.0 | 250 | 1.7 | 2 | 51.0 | 0.08 | 0.12 | 56 | – |
| B906 | 3/8 | 10 | 0.64 | 16.3 | 250 | 1.7 | 3 | 76.0 | 0.09 | 0.13 | 56 | 82* |
| B908 | 1/2 | 12.5 | 0.78 | 19.8 | 250 | 1.7 | 3 | 76.0 | 0.13 | 0.19 | 56 | 82* |
| B910 | 3/4 | 16 | 0.92 | 23.4 | 250 | 1.7 | 4 | 102.0 | 0.20 | 0.30 | 56 | 82* |



WARNING

This product can expose you to chemicals including N-Methylpyrrolidone, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.