

















Fittings - Permanent Crimp

PAGE Series

| | | | | | |
|--|--|---|--|--|---|
| PAGE Series Permanent | CL Female Cam & Groove  E-66 | E Male Cam & Groove  E-67 | FBS Female Sanitary Bevel Seat  E-67 | FIL Female I-Line® Sanitary  E-68 | FJX Female JIC 37° Swivel  E-69 |
| | FORFS Female Seat-Lok™ Swivel Short  E-69 | FP Female NPTF Pipe Rigid  E-68 | MBS Male Sanitary Bevel Seat  E-67 | MIL Male I-Line® Sanitary  E-68 | MP Male NPTF Pipe Rigid  E-69 |
| | MSAN Mini Sanitary Flange  E-71 | PF ANSI Flange  E-70 | PLCF Female A-Lok® Compression  E-70 | SAN Sanitary Flange & Step Downs  E-71 | SFR Flange Retainer  E-71 |
| | TUBE A-Lok Male Standpipe Rigid "V" Notch  E-70 | PAGE fittings require a PAGE collar. See pg. E-66. | | | |

The PAGE fitting call-out does not follow the traditional Parker fitting nomenclature. The end size and hose size are reversed.



WARNING

This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Fittings - Permanent Crimp

PAGE Series

PAGE Fitting Collars - By Size



| Hose Size | Collar # Size | 04 | 06 | 08 | 12 | 14 | 16 | 20 | 24 | 32 | 40 | 48 | 64 |
|--------------|---------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| STW STB | ST300 | ST300 | ST300 | ST300 | ST300 | ST300 | ST300 | ST300 | ST300 | | | | |
| SCW SCB | SC300 | ST300 | SC300 | SC300 | SC300 | SC300 | SC300 | SC300 | SC300 | SC300 | | | |
| SCWV SCBV | SC300 | | | SC300 | SC300 | SC300 | SC300 | SC300 | SC300 | SC300 | SC300 | SC300 | SC300 |
| PCW PCB | PC300 | PC300 | PC300 | PC300 | PC300 | PC300 | PC300 | PC300 | PC300 | PC300 | | | |

Construction: Stainless Steel. Also available in carbon steel "CS".

Inserts & Collars Sold Separately

Examples:

If you need a Female JIC Swivel Fitting for a 08-SCW Hose (1/2" Convolution), place an order for (1) 08-08 FJX-S and (1) 08-SC300.

If you need a Male Pipe Fitting for a 12-STW Hose, place an order for (1) 12-12 MP-S and (1) 12-ST300.

PAGE Fitting Collars - By Style




| Size | ST300 For use with STW, STB | SC300 For use with SCW, SCB, SCWV, SCBV | PC300 For use with PCW, PCB |
|--------|-----------------------------------|---|-----------------------------------|
| 1/4" | 04-ST300 | 04-SC300 | 04-PC300 |
| 3/8" | 06-ST300 | 06-SC300 | 06-PC300 |
| 1/2" | 08-ST300 | 08-SC300 | 08-PC300 |
| 3/4" | 12-ST300 | 12-SC300 | 12-PC300 |
| 1" | 16-ST300 | 16-SC300 | 16-PC300 |
| 1-1/4" | 20Z-ST300 | 20-SC300 | 20-PC300 |
| 1-1/2" | 24Z-ST300 | 24-SC300 | 24-PC300 |
| 2" | — | 32-SC300 | 32-PC300 |
| 3" | — | 48-SC300 | — |
| 4" | — | 64-SC300 | — |

Construction: Stainless Steel. Also available in carbon steel "CS".

The PAGE fitting call-out does not follow the traditional Parker fitting nomenclature. The end size and hose size are reversed.

CL Female Cam & Groove



| Part Number | Hose Size | | A | | E | |
|-------------|-----------|-----|------|-----|------|-----|
| | inch | mm | inch | mm | inch | mm |
| 16-16CL-S | 1 | 25 | 4.2 | 107 | 1.44 | 37 |
| 24-24CL-S | 1-1/2 | 38 | 5.2 | 132 | 2.10 | 53 |
| 32-32CL-S | 2 | 51 | 6.0 | 152 | 2.48 | 63 |
| 48-48CL-S | 3 | 76 | 7.2 | 183 | 3.60 | 91 |
| 64-64CL-S | 4 | 102 | 7.8 | 198 | 4.70 | 119 |

Construction: Stainless Steel.

NOTE: Also available as encapsulated female cam under part number TEC and TECL.




WARNING

This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Fittings - Permanent Crimp

PAGE Series

E Male Cam & Groove




Construction: Stainless Steel.

| Part Number | Hose Size | | A | | E | |
|-------------|-----------|-----|------|-----|------|-----|
| | inch | mm | inch | mm | inch | mm |
| 12-12E-S | 3/4 | 19 | 2.60 | 66 | 1.26 | 32 |
| 16-16E-S | 1 | 25 | 2.91 | 74 | 1.44 | 37 |
| 20-20E-S | 1-1/4 | 32 | 3.64 | 93 | 1.78 | 45 |
| 24-24E-S | 1-1/2 | 38 | 4.03 | 102 | 2.10 | 53 |
| 32-32E-S | 2 | 51 | 4.75 | 121 | 2.48 | 63 |
| 48-48E-S | 3 | 76 | 5.75 | 146 | 3.60 | 91 |
| 64-64E-S | 4 | 102 | 5.88 | 149 | 4.70 | 119 |

NOTE: Also available as encapsulated female cam under part number TEC and TECL.

FBS Female Sanitary Bevel Seat




Construction: Stainless Steel.

| Part Number | Acme Thread | Hose Size | | A | |
|-------------|-------------|-----------|-----|------|-----|
| | | inch | mm | inch | mm |
| 16-16FBS-S | 1-1/2-8 | 1 | 25 | 2.74 | 70 |
| 24-24FBS-S | 2-8 | 1-1/2 | 38 | 3.41 | 87 |
| 32-32FBS-S | 2-1/2-8 | 2 | 51 | 3.94 | 100 |
| 40-40FBS-S | 3-8 | 2-1/2 | 64 | 4.37 | 110 |
| 48-48FBS-S | 3-1/2-8 | 3 | 76 | 4.85 | 123 |
| 64-64FBS-S | 4-5/8-6 | 4 | 102 | 5.24 | 133 |

NOTE: Also available as encapsulated female cam under part number TEC and TECL.

The PAGE fitting call-out does not follow the traditional Parker fitting nomenclature. The end size and hose size are reversed.

MBS Male Sanitary Bevel Seat



Construction: Stainless Steel.

| Part Number | Acme Thread | Hose Size | | A | |
|-------------|-------------|-----------|-----|------|-----|
| | | inch | mm | inch | mm |
| 16-16MBS-S | 1-1/2-8 | 1 | 25 | 2.74 | 70 |
| 24-24MBS-S | 2-8 | 1-1/2 | 38 | 3.41 | 87 |
| 32-32MBS-S | 2-1/2-8 | 2 | 51 | 3.94 | 100 |
| 40-40MBS-S | 3-8 | 2-1/2 | 64 | 4.37 | 110 |
| 48-48MBS-S | 3-1/2-8 | 3 | 76 | 4.85 | 123 |
| 64-64MBS-S | 4-5/8-6 | 4 | 102 | 5.24 | 133 |

NOTE: Also available as encapsulated female cam under part number TEC and TECL.




WARNING

This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Fittings - Permanent Crimp

PAGE Series


FIL Female I-Line® Sanitary



Construction: Stainless Steel.

| Part Number | Hose Size | | A | | Flange Size C | | D | |
|-------------|-----------|----|------|-----|---------------|----|------|----|
| | inch | mm | inch | mm | inch | mm | inch | mm |
| 16-16FIL-S | 1 | 25 | 2.60 | 66 | 1.25 | 32 | 2.00 | 51 |
| 24-24FIL-S | 1-1/2 | 38 | 3.43 | 87 | 1.76 | 45 | 2.00 | 51 |
| 32-32FIL-S | 2 | 51 | 4.23 | 107 | 2.26 | 57 | 2.64 | 67 |
| 40-40FIL-S | 2-1/2 | 25 | 2.60 | 66 | 1.25 | 32 | 2.00 | 51 |
| 48-48FIL-S | 3 | 38 | 3.43 | 87 | 1.76 | 45 | 2.00 | 51 |

MIL Male I-Line® Sanitary




Construction: Stainless Steel.

| Part Number | Hose Size | | A | | Flange Size C | | D | |
|-------------|-----------|----|------|-----|---------------|----|------|----|
| | inch | mm | inch | mm | inch | mm | inch | mm |
| 16-16MIL-S | 1 | 25 | 2.60 | 66 | 1.25 | 32 | 2.00 | 51 |
| 24-24MIL-S | 1-1/2 | 38 | 3.43 | 87 | 1.76 | 45 | 2.00 | 51 |
| 32-32MIL-S | 2 | 51 | 4.23 | 107 | 2.26 | 57 | 2.64 | 67 |
| 40-40MIL-S | 2-1/2 | 64 | 4.42 | 112 | 2.76 | 70 | 3.31 | 84 |
| 48-48MIL-S | 3 | 76 | 4.84 | 123 | 3.31 | 84 | 3.87 | 98 |

The PAGE fitting call-out does not follow the traditional Parker fitting nomenclature. The end size and hose size are reversed.

FP Female NPTF Pipe Rigid



Construction: Stainless Steel.

| Part Number | Thread Size | Hose Size | | A | | H Hex |
|-------------|--------------|-----------|----|------|-----|--------|
| | | inch | mm | inch | mm | |
| 04-04FP-S | 1/4-18 | 1/4 | 6 | 1.63 | 41 | 3/4 |
| 06-06FP-S | 3/8-18 | 3/8 | 10 | 1.73 | 44 | 7/8 |
| 08-08FP-S | 1/2-14 | 1/2 | 13 | 2.25 | 57 | 1-1/16 |
| 12-12FP-S | 3/4-14 | 3/4 | 19 | 2.60 | 66 | 1-5/16 |
| 16-16FP-S | 1-11 1/2 | 1 | 25 | 2.85 | 72 | 1-5/8 |
| 20-20FP-S | 1 1/4-11 1/2 | 1-1/4 | 32 | 3.50 | 89 | 2 |
| 24-24FP-S | 1 1/2-11 1/2 | 1-1/2 | 38 | 3.63 | 92 | 2-3/8 |
| 32-32FP-S | 2-11 1/2 | 2 | 51 | 4.25 | 108 | 2-7/8 |




WARNING

This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Fittings - Permanent Crimp

PAGE Series

MP Male NPTF Pipe Rigid




Construction: Stainless Steel.

| Part Number | Thread Size | Hose Size | | A | | H Hex |
|-------------|--------------|-----------|-----|------|-----|-------|
| | | inch | mm | inch | mm | inch |
| 04-04MP-S | 1/4-18 | 1/4 | 6 | 1.63 | 41 | 9/16 |
| 06-06MP-S | 3/8-18 | 3/8 | 10 | 1.76 | 45 | 11/16 |
| 08-08MP-S | 1/2-14 | 1/2 | 13 | 2.34 | 59 | 7/8 |
| 12-12MP-S | 3/4-14 | 3/4 | 19 | 2.59 | 66 | 1-1/8 |
| 16-16MP-S | 1-11 1/2 | 1 | 25 | 3.00 | 76 | 1-3/8 |
| 20-20MP-S | 1 1/4-11 1/2 | 1-1/4 | 32 | 3.39 | 86 | 1-3/4 |
| 24-24MP-S | 1 1/2-11 1/2 | 1-1/2 | 38 | 3.89 | 99 | 2 |
| 32-32MP-S | 2-11 1/2 | 2 | 51 | 4.58 | 116 | 2-1/2 |
| 40-40MP-S | 2-1/2 8 | 2-1/2 | 64 | 5.28 | 134 | 3 |
| 48-48MP-S | 3-8 | 3 | 76 | 5.93 | 151 | 3-3/4 |
| 64-64MP-S | 4-8 | 4 | 102 | 6.82 | 173 | 4-5/8 |

The PAGE fitting call-out does not follow the traditional Parker fitting nomenclature. The end size and hose size are reversed.


FJX Female JIC 37° Swivel



Construction: Stainless Steel.

| Part Number | Thread Size | Hose Size | | A | | H Hex |
|-------------|-------------|-----------|----|------|-----|-------|
| | | inch | mm | inch | mm | inch |
| 04-04FJX-S | 7/16-20 | 1/4 | 6 | 1.44 | 37 | 9/16 |
| 06-06FJX-S | 9/16-18 | 3/8 | 10 | 1.65 | 42 | 11/16 |
| 08-08FJX-S | 3/4-16 | 1/2 | 13 | 2.13 | 54 | 7/8 |
| 12-12FJX-S | 1-1/16-12 | 3/4 | 19 | 2.54 | 65 | 1-1/4 |
| 16-16FJX-S | 1-5/16-12 | 1 | 25 | 2.76 | 70 | 1-1/2 |
| 20-20FJX-S | 1-5/8-12 | 1-1/4 | 32 | 3.25 | 83 | 2 |
| 24-24FJX-S | 1-7/8-12 | 1-1/2 | 38 | 3.73 | 95 | 2-1/4 |
| 32-32FJX-S | 2-1/2-12 | 2 | 51 | 4.55 | 116 | 2-7/8 |
| 40-40FJX-S | 3-12 | 2-1/2 | 64 | 4.76 | 121 | 3-3/8 |

FORFS Female Seal-Lok® Swivel Short



Construction: Stainless Steel.

| Part Number | Thread Size | Hose Size | | A | | C | | H Hex | J Hex |
|--------------|-------------|-----------|----|------|-----|------|----|-------|-------|
| | | inch | mm | inch | mm | inch | mm | inch | inch |
| 04-04FORFS-S | 9/16-18 | 1/4 | 6 | 1.50 | 38 | .32 | 8 | 9/16 | 11/16 |
| 06-06FORFS-S | 11/16-16 | 3/8 | 10 | 1.85 | 47 | .32 | 8 | 11/16 | 13/16 |
| 08-08FORFS-S | 13/16-16 | 1/2 | 13 | 2.00 | 51 | .43 | 11 | 13/16 | 15/16 |
| 12-12FORFS-S | 1-3/16-12 | 3/4 | 19 | 2.30 | 58 | .57 | 14 | 1-1/8 | 1-3/8 |
| 16-16FORFS-S | 1-7/16-12 | 1 | 25 | 2.50 | 64 | .58 | 15 | 1-3/8 | 1-5/8 |
| 24-24FORFS-S | 2-12 | 1-1/2 | 38 | 3.98 | 101 | .59 | 15 | 2 | 2-1/4 |



WARNING

This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Fittings - Permanent Crimp

PAGE Series

A Hose

B Tubing Thermoplastic

C Coiled Air Hose & Fittings


D Transportation

M Fittings

F Tooling, Equipment & Accessories

G General Technical


PLCF Female A-LOK® Compression (With Nut & Ferrules)



Construction: Stainless Steel.

| Part Number | Thread Size | Hose Size | | A | | J Hex | H Hex |
|-------------|-------------|-----------|----|------|----|-------|-------|
| | | inch | mm | inch | mm | inch | inch |
| 04-04PLCF-S | 7/16-20 | 1/4 | 6 | 1.52 | 39 | 9/16 | 9/16 |
| 06-06PLCF-S | 9/16-20 | 3/8 | 10 | 1.63 | 41 | 11/16 | 11/16 |
| 08-08PLCF-S | 3/4-20 | 1/2 | 13 | 2.05 | 52 | 7/8 | 7/8 |
| 12-12PLCF-S | 1-20 | 3/4 | 19 | 2.30 | 58 | 1-1/8 | 1-1/8 |
| 16-16PLCF-S | 1-5/16-20 | 1 | 25 | 2.57 | 65 | 1-3/8 | 1-1/2 |

TUBE A-LOK® Male Standpipe Rigid with "V" Notch




Construction: Stainless Steel.

| Part Number | Diameter R | Hose Size | | A | | C | | D | | H Hex |
|-------------|------------|-----------|----|------|----|------|----|------|----|-------|
| | | inch | mm | inch | mm | inch | mm | inch | mm | inch |
| 04-04TUBE-S | 1/4 | 1/4 | 6 | 1.75 | 45 | .18 | 5 | .66 | 17 | 7/16 |
| 06-06TUBE-S | 3/8 | 3/8 | 10 | 2.06 | 52 | .25 | 6 | .85 | 2 | 5/8 |
| 08-08TUBE-S | 1/2 | 1/2 | 13 | 2.56 | 65 | .34 | 9 | .97 | 25 | 3/4 |
| 12-12TUBE-S | 3/4 | 3/4 | 19 | 2.86 | 73 | .40 | 10 | 1.02 | 26 | 1-1/8 |
| 16-16TUBE-S | 1 | 1 | 25 | 3.34 | 85 | .52 | 13 | 1.30 | 33 | 1-3/8 |
| 20-20TUBE-S | 1-1/4 | 1-1/4 | 32 | 4.05 | 10 | .50 | 13 | 1.75 | 45 | 1-3/4 |

The PAGE fitting call-out does not follow the traditional Parker fitting nomenclature. The end size and hose size are reversed.

PF ANSI B16.5 Flange



Construction: 316 Stainless Steel.


| Part Number | Flange Diameter A | | Hose Size | | Bolt Spacing B | |
|-------------|-------------------|-----|-----------|-----|----------------|-----|
| | inch | mm | inch | mm | inch | mm |
| 08-PF156 | 3-1/2 | 89 | 1/2 | 13 | 2-3/8 | 60 |
| 12-PF156 | 3-7/8 | 98 | 3/4 | 19 | 2-3/4 | 70 |
| 16-PF156 | 4-1/4 | 108 | 1 | 25 | 3-1/8 | 79 |
| 20-PF156 | 4-5/8 | 117 | 1-1/4 | 32 | 3-1/2 | 89 |
| 24-PF156 | 5 | 127 | 1-1/2 | 38 | 3-7/8 | 98 |
| 32-PF156 | 6 | 152 | 2 | 51 | 4-3/4 | 120 |
| 40-PF156 | 7 | 178 | 2-1/2 | 64 | 5-1/2 | 140 |
| 48-PF156 | 7-1/2 | 191 | 3 | 76 | 6 | 152 |
| 64-PF156 | 9 | 229 | 4 | 102 | 7-1/2 | 191 |

WARNING This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Fittings - Permanent Crimp

PAGE Series


SFR Flange Retainer



Construction: Stainless Steel.

| Part Number | Flange Diameter | | Hose Size | | A | | Bolt Spacing E | |
|-------------|-----------------|-----|-----------|-----|------|-----|----------------|-----|
| | inch | mm | inch | mm | inch | mm | inch | mm |
| 08-08SFR-S | 3-1/2 | 89 | 1/2 | 13 | 2.30 | 58 | 2-3/8 | 60 |
| 12-12SFR-S | 3-7/8 | 98 | 3/4 | 19 | 2.60 | 66 | 2-3/4 | 70 |
| 16-16SFR-S | 4-1/4 | 108 | 1 | 25 | 3.00 | 76 | 3-1/8 | 79 |
| 20-20SFR-S | 4-5/8 | 117 | 1-1/4 | 32 | 3.25 | 83 | 3-1/2 | 89 |
| 24-24SFR-S | 5 | 127 | 1-1/2 | 38 | 3.65 | 93 | 3-7/8 | 98 |
| 32-32SFR-S | 6 | 152 | 2 | 51 | 4.25 | 108 | 4-3/4 | 120 |
| 40-40SFR-S | 7 | 178 | 2-1/2 | 64 | 5.00 | 127 | 5-1/2 | 140 |
| 48-48SFR-S | 7-1/2 | 191 | 3 | 76 | 5.50 | 140 | 6 | 152 |
| 64-64SFR-S | 9 | 229 | 4 | 102 | 7.00 | 178 | 7-1/2 | 191 |


MSAN Mini Sanitary Flange



Construction: Stainless Steel.

| Part Number | Hose Size | | A | | Flange Size D | |
|-------------|-----------|----|------|----|---------------|----|
| | inch | mm | inch | mm | inch | mm |
| 04-04MSAN-S | 1/4 | 6 | 1.41 | 36 | .98 | 25 |
| 04-08MSAN-S | 1/4 | 6 | 1.50 | 38 | .98 | 25 |
| 06-06MSAN-S | 3/8 | 10 | 1.53 | 39 | .98 | 25 |
| 06-08MSAN-S | 3/8 | 10 | 1.53 | 39 | .98 | 25 |
| 06-12MSAN-S | 3/8 | 10 | 1.66 | 42 | .98 | 25 |
| 08-08MSAN-S | 1/2 | 13 | 1.90 | 48 | .98 | 25 |
| 08-12MSAN-S | 1/2 | 13 | 1.94 | 49 | .98 | 25 |
| 12-12MSAN-S | 3/4 | 19 | 2.16 | 55 | .98 | 25 |
| 16-16MSAN-S | 1 | 25 | 2.27 | 58 | 1.34 | 34 |

SAN Sanitary Flange & Step-Downs



Construction: Stainless Steel.

| Part Number | Hose Size | | A | | Flange Size D | |
|-------------|-----------|-----|------|-----|---------------|-----|
| | inch | mm | inch | mm | inch | mm |
| 08-08SAN-S | 1/2 | 13 | 2.11 | 54 | 1.98 | 50 |
| 08-16SAN-S | 1/2 | 13 | 2.11 | 54 | 1.98 | 50 |
| 08-24SAN-S | 1/2 | 13 | 2.34 | 59 | 1.98 | 50 |
| 12-12SAN-S | 3/4 | 19 | 2.32 | 59 | 1.98 | 50 |
| 16-16SAN-S | 1 | 25 | 2.45 | 62 | 1.98 | 50 |
| 12-24SAN-S | 3/4 | 19 | 2.34 | 59 | 1.98 | 50 |
| 16-24SAN-S | 1 | 25 | 2.32 | 59 | 1.98 | 50 |
| 24-24SAN-S | 1-1/2 | 38 | 3.1 | 79 | 1.98 | 50 |
| 24-32SAN-S | 1-1/2 | 38 | 3.12 | 79 | 2.52 | 64 |
| 32-32SAN-S | 2 | 51 | 3.67 | 93 | 2.52 | 64 |
| 40-40SAN-S | 2-1/2 | 64 | 4 | 102 | 3.05 | 77 |
| 48-48SAN-S | 3 | 76 | 4.5 | 114 | 3.58 | 91 |
| 64-64SAN-S | 4 | 102 | 4.75 | 121 | 4.68 | 119 |

The PAGE fitting call-out does not follow the traditional Parker fitting nomenclature.

The end size and hose size are reversed.



WARNING

This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.