

# LP Gas Vapor Hose

## Series 7122



Series 7122 is a flexible, lightweight, light duty hose connector for transfer of LP Gas vapor in space heaters for chicken brooders and other light applications. The hose construction incorporates multiple textile plies of reinforcement for flexibility and kink resistance. The perforated cover is resistant to mild chemicals, oil and ozone.

**NOTES:**

- Do not use to transfer liquid LP gas in gas grill or other applications requiring Underwriters Laboratories (UL) or Canadian Standards Association (CSA) performance or listing.
- Refer to the Safety and Technical Information section of this catalog for safety, handling and use information.

**Series 7122 and Natural Gas:** Series 7122 may be used for natural gas service, but ONLY under ALL of the following conditions:

- 1) The application must be in a well-ventilated environment: Outdoors, or indoors with significant continuous air movement.
- 2) Series 7122 is not to replace fixed/rigid pipe where that material is more appropriate due to reduced permeation and overall strength and durability. Use rigid pipe, non-permeable tubing or hose with barrier constructions to convey natural gas whenever possible.

### Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at [www.parker.com/crimpsource](http://www.parker.com/crimpsource).

#	ID	ID	Reinf	OD	OD	Approx	Approx	Min	Min	Max	Max	Perm	Nom	Std	Pkg
Part Number	(in)	(mm)	Layers	(in)	(mm)	Wt (lbs/ft)	Wt (kg/m)	Bend Rad (in)	Bend Rad (mm)	WP (psi)	WP (bar)	Cplg Rec *	Std Pack Qty (ft)		Type
7122-38200	3/8	9.5	2	0.7	16.7	0.15	0.22	4	97	125	9	HY	700		Reel

**WARNING:** This product can expose you to chemicals including DEHP, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

**Tube:** Black nitrile

**Reinforcement:** Multiple textile plies

**Cover:** Red chloroprene; perforated smooth finish

**Temp. Range:** -20°F to +160°F (-29°C to +71°C) (The hose construction is capable of this rating, but LP Gas should NEVER be conveyed over 140°F/60°C)

**Brand Method:** Black ink

**Brand Example:** PARKER SERIES 7122 LPG VAPOR HOSE  
125 PSI MAX WP

**Design Factor:** 4:1

**Industry Standards:** None applicable

**Applications:**

- LP gas – vapor ONLY
- Chicken brooders, space heaters
- Agriculture, light industrial

**Vacuum:** Not recommended

**Compare to:** Gates LPG Vapor