

SIGMA-ULTRAVAC-SBR™









SBR Vacuum Hose

Ultravac SBR™ is a specially compounded vacuum hose that is suitable for use in a multitude of wet and dry material applications. Being lightweight and flexible, Ultravac SBR™ is the ideal hose for vacuum trucks, hydro-excavators, and sewer cleaning equipment. Its static dissipative carbon black tube makes it suitable for handling sand, gravel, dry cement, iron chips, grains and other light abrasives.



TECHNICAL DATA

Construction	Static dissipating, SBR blended tube with a rigid right-handed PVC helix
Safety Factor	3:1
Temperature	-40°F to +158°F
Branding	SIGMA SERIES - ULTRAVAC SBR-<ID>-LOT
Compared To	180 AR
Features	Excellent flexibility when compared to PVC/polyurethane hose

 I.D.	 Part Number	 O.D.	 Std. Length	 Working Pressure (psi)	 Vacuum (in./HG)	 Bend Radius	 Lbs./Ft.
1 ½"	SP-SBR-1.5	1.82"	100'	45	29	2"	0.35
2"	SP-SBR-2.0	2.35"	100'	40	29	3"	0.52
2 ½"	SP-SBR-2.5	2.95"	100'	35	29	3"	0.90
3"	SP-SBR-3.0	3.5"	100'	35	29	3"	1.08
4"	SP-SBR-4.0	4.63"	50', 100'	30	29	5"	1.80
5"	SP-SBR-5.0	5.76"	50', 100'	30	28	5"	2.45
6"	SP-SBR-6.0	6.73"	50', 100'	30	28	9"	3.05
8"	SP-SBR-8.0	9.04"	50'	30	27	15"	5.63