

SIGMA-URE-B™









Polyurethane Material Handling Hose with PVC Cover

Abrasion-resistant, polyurethane tube for material handling in dry applications, such as sandblast recovery lines, roof rock cleaning and other abrasive applications. Made of static-dissipating material that remains flexible at low temperatures for ease of handling.



TECHNICAL DATA

Construction	Black, flexible PVC and smooth with black, rigid, right-handed helix and smooth, polyurethane liner
Safety Factor	3:1
Temperature	-40°F to +150°F
Compared To	UBK
Safety Note	Service temperature depends on actual application

 I.D.	 Part Number	 O.D.	 Std. Length	 Working Pressure (psi)	 Vacuum (in./Hg)	 Bend Radius	 Lbs./Ft.
2"	SPVC-URE-B-2.0	2.40"	50'/100'	40	29	2"	0.51
2-1/2"	SPVC-URE-B-2.5	3.10"	50'/100'	40	29	4"	0.77
3"	SPVC-URE-B-3.0	3.55"	50'/100'	40	29	4"	0.87
4"	SPVC-URE-B-4.0	4.68"	50'/100'	35	29	6"	1.55
5"	SPVC-URE-B-5.0	5.71"	50'/100'	30	28	10"	2.30
6"	SPVC-URE-B-6.0	7.05"	20'/50'/100'	30	28	12"	3.40
8"	SPVC-URE-B-8.0	9.05"	20'/50'	30	28	15"	4.88