

GAMMA™-BULK

Dry Bulk Material Discharge Hose

Soft-wall discharge hose used in the transfer of dry materials and slurries. Ideal for dry cement, pebble lime and other abrasive media.



TECHNICAL DATA

| | | |
|---------------|---|--|
| Tube | Black, abrasion-resistant NR/SBR, static-dissipating materials | |
| Cover | Black, abrasion-resistant NR/SBR | |
| Reinforcement | High tensile tire cord plies | |
| Safety Factor | 4:1 | |
| Temperature | -40°F to +180°F | |
| Branding | TEXCEL® GAMMA™-BULK - DRY CEMENT DISCHARGE HOSE STATIC CONDUCTIVE XX TUBE 75 PSI W.P. | |

| I.D. | Part Number | Tube Gauge | O.D. | Std. Length | Working Pressure (psi) | Number of Plies | Lbs./Ft. |
|------|--------------|------------|----------|-------------|------------------------|-----------------|----------|
| 4" | GBU75S1B-4-4 | 1/8" | 4-28/64" | 100' | 75 | 2 | 1.72 |
| | GBU75S1B-4-6 | 3/16" | 4-40/64" | 100' | 75 | 2 | 2.20 |
| | GBU75S1B-4-8 | 1/4" | 4-51/64" | 100' | 75 | 2 | 2.61 |
| 5" | GBU75S1B-5-4 | 1/8" | 5-30/64" | 100' | 75 | 2 | 2.27 |
| | GBU75S1B-5-6 | 3/16" | 5-40/64" | 100' | 75 | 2 | 2.75 |
| | GBU75S1B-5-8 | 1/4" | 5-51/64" | 100' | 75 | 2 | 3.25 |