

# GAMMA™-COMM DISCHARGE

## Commodity Discharge Hose









Soft-wall hose designed with a high abrasion-resistant tube. Ideal for applications where the discharging of wet or dry abrasive media is required.



### TECHNICAL DATA

Tube	Black, abrasion-resistant NR/SBR, static-dissipating materials
Cover	Black, SBR
Reinforcement	High tensile tire cord plies
Safety Factor	4:1
Temperature	-40°F to +180°F
Branding	TEXCEL® GAMMA™-COMM DISCH - BULK COMMODITY DISCHARGE HOSE STATIC CONDUCTIVE TUBE XXX PSI W.P.



							
I.D.	Part Number	O.D.	Tube Gauge	Std. Length	Working Pressure (psi)	Number of Plies	Lbs./Ft.
2"	GCOMM-D-B1-2.0	2-45/64"	3/16"	100'	150	2	1.51
2-1/2"	GCOMM-D-B1-2.5	3-13/64"	3/16"	100'	125	2	1.82
3"	GCOMM-D-B1-3.0	3-46/64"	3/16"	100'	125	2	2.20
4"	GCOMM-D-B1-4.0	4-45/64"	3/16"	100'	100	2	2.79
4-1/2"	GCOMM-D-B1-4.5	5-13/64"	1/4"	100'	75	2	3.40
5"	GCOMM-D-B1-5.0	5-45/64"	1/4"	100'	75	2	3.78
6"	GCOMM-D-B1-6.0	6-45/64"	1/4"	100'	75	2	4.06