

# TEX-CRETE

Textile Concrete Hose

Designed to provide the ultimate combination of handling ease, abuse resistance and long service life required for plaster, grout and concrete placement applications. Ideal for concrete pumping applications.



## TECHNICAL DATA

Tube	Black, wear-resistant, GUM/SBR blend	
Cover	Black, SBR, cut and gouge-resistant	
Reinforcement	Multiple plies of high tensile tire cord	
Safety Factor	2:1 (per ASME standards)	
Temperature	-40°F to +200°F	
Branding	TEXCEL® TEX-CRETE - FABRIC CONCRETE PLACEMENT HOSE 1230 PSI (85 BAR) W.P. XXX LBS/FT (F.W.C)	

I.D.	Part Number	O.D.	Std. Length	Working Pressure psi/bar	Burst Pressure psi/bar	Bend Radius	Lbs./Ft.
1-1/4"	CRETE-1.25	2"	100'	1230/85	2460/170	8"	0.86
1-1/2"	CRETE-1.5	2-12/64"	100'	1230/85	2460/170	10"	0.92
2"	CRETE-2.0	2-49/64"	50'/100'	1230/85	2460/170	12"	1.45
2-1/2"	CRETE-2.5	3-22/64"	100'	1230/85	2460/170	14"	1.71
3"	CRETE-3.0	4"	50'/100'	1230/85	2460/170	15"	2.40
3-1/2"	CRETE-3.5	4-31/64"	100'	1230/85	2460/170	16"	3.07
4"	CRETE-4.0	5-10/64"	100'	1230/85	2460/170	18"	4.06
4-1/2"	CRETE-4.5	5-38/64"	100'	1230/85	2460/170	21"	4.22
5"	CRETE-5.0	6-19/64"	100'	1230/85	2460/170	24"	5.60
6"	CRETE-6.0	7-21/64"	100'	1230/85	2460/170	30"	6.80