



SIGMA-PB DISCHARGE™

Blue PVC Lay-Flat Discharge Hose

Premium-quality, lightweight, lay-flat PVC hose that is economical and easy to handle. Excellent for pump discharge applications.



TECHNICAL DATA

Construction	Blue, homogeneous virgin PVC with high tensile polyester yarn
Safety Factor	3:1
Temperature	-10°F to +120°F
Branding	TEXCEL® SIGMA-PB DISCHARGE™ - WATER DISCHARGE HOSE -<ID>-LOT
Safety Note	Service temperature depends on actual application

 I.D.	 Part Number	 Std. Length	 Working Pressure (psi)	 Lbs./Ft.
1"	SPVC-PB-1.0-300	300'	90	0.10
1-¼"	SPVC-PB-1.25-300	300'	85	0.12
1-½"	SPVC-PB-1.5-300	300'	70	0.14
2"	SPVC-PB-2.0-300	300'	65	0.18
2-½"	SPVC-PB-2.5-300	300'	60	0.26
3"	SPVC-PB-3.0-300	300'	55	0.31
4"	SPVC-PB-4.0-300	300'	55	0.36
5"	SPVC-PB-5.0-300	300'	45	0.64
6"	SPVC-PB-6.0-300	300'	45	0.73
8"	SPVC-PB-8.0-300	300'	45	1.21
10"	SPVC-PB-10.0-100	100'	35	1.81
12"	SPVC-PB-12.0-100	100'	30	1.95

SIGMA-RH DISCHARGE™

Heavy-Duty Red PVC Lay-Flat Discharge Hose

A heavy-duty PVC lay-flat hose designed for higher pressure applications. The exclusive "through the weave" process ensures the highest quality and durability. An ideal hose for pump discharge, tank cleaning, dewatering, irrigation and wash down applications.



TECHNICAL DATA

Tube and Cover	Red, homogeneous virgin PVC
Reinforcement	High tensile polyester yarn
Safety Factor	3:1
Temperature	-10°F to +120°F
Branding	TEXCEL® SIGMA-RH DISCHARGE™ - HEAVY DUTY WATER DISCHARGE HOSE -<ID>-LOT
Safety Note	Service temperature depends on actual application

 I.D.	 Part Number	 Std. Length	 Working Pressure (psi)	 Lbs./Ft.
1-½"	SPVC-RH-1.5-300	300'	150	0.20
2"	SPVC-RH-2.0-300	300'	150	0.28
3"	SPVC-RH-3.0-300	300'	150	0.57
4"	SPVC-RH-4.0-300	300'	130	0.67
6"	SPVC-RH-6.0-300	300'	120	1.34
8"	SPVC-RH-8.0-300	300'	90	1.88